



Specification IEC 60034-1
Manufacturer AmTecs
Motor type AMAS-R-IE2 80 G2
Rated power 1.1 kW S1 Duty
Speed 2850 rpm
Voltage 220V
Frequency 50 Hz
Connection Single Phase
Full load current 6.13 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M20x1.5
Construction Aluminium
Weight 11.2 Kg
Type number
Warranty
Run Capacitor 30uf/450V

Efficiency class IE2
Load data 100%
Efficiency 79.6 %
Power factor 0.98
Sound pressure level (1m) 75 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)
Full load torque 3.69 Nm
Starting / Full load torque 0.4
Pull up / Full load torque
Pull out / Full load torque 1.9

Starting / Full load current (DOL)
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6204
Bearing NDE 6204

Protection Device **Thermal Reset Switch**

AmTecs Ltd	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk