



Remarks:

- 1. Glands: 1 off M20 x 1.5 and 1 off M16 x 1.5, Blanking plug 1 off M20 x 1.5

DRAWN James Souter	16/01/2024	AMTECS LTD	
CHECKED Oliver Young			
QA		TITLE	
MFG		AMA3-IE3 80 (B34L)	
APPROVED		SIZE A3	DWG NO AMA3-IE3 80 (B34L)
		SCALE 1 / 4	REV
		SHEET 1 OF 1	

Specification IEC 60034-1
Manufacturer AmTecs
Motor type AMA3-IE3 80K2
Rated power 0.75 kW S1 Duty
Speed 2900 rpm
Voltage 220V / 400V
Frequency 50 Hz
Connection Delta / Star
Full load current 2.85 A / 1.64 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M20x1.5
Construction Aluminium
Weight 13.5 Kg
Type number
Warranty

Efficiency class IE3
Load data 100%
Efficiency 80.7 %
Power factor 0.82
Sound pressure level (1m) 58 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)
Full load torque 2.47 Nm
Starting / Full load torque 2.8
Pull up / Full load torque
Pull out / Full load torque 3
Starting / Full load current (DOL) 8
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6204
Bearing NDE 6204

AmTecs Ltd	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk