



**AmTECS LTD**

TITLE  
**AM1 (B35)**

SIZE  
**A3**

SCALE  
**1 / 3.5**

DWG NO

REV

SHEET 1 OF 1

This drawing serves only as a sketch to show dimensions.  
The product delivered may differ. A detailed description of the product can be found below.

Specification **IEC 60034-1**

Manufacturer **AmTecs**

Motor type **AM1-IE2 200L4**

Rated power **30 kW S1 Duty**

Speed **1475 rpm**

Voltage **400V / 690V**

Frequency **50 Hz**

Connection **Delta / Star**

Full load current **54.6 A / 31.6 A**

No-load current

Enclosure **IP55**

Insulation class **F (temp. rise B)**

Max. ambient temp **40 °C**

Max. altitude **1000 mtr above sea level**

Comment

Cable entry **M40 x 1.5**

Construction **Cast Iron**

Weight **247 Kg**

Type number

Warranty

Efficiency class **IE2**

Load data **100%**

Efficiency **92.3 %**

Power factor **0.86**

Sound pressure level (1m) **76 dB(A)**

Resistance R20 (open)

Resistance R20 (Delta)

Full load torque **194 Nm**

Starting / Full load torque **2.4**

Pull up / Full load torque

Pull out / Full load torque **2.9**

Starting / Full load current (DOL) **7.1**

Starting / Full load current (Y/D)

Rotor Inertia

Bearing DE **6312**

Bearing NDE **6312**

|  |                    |
|--|--------------------|
| <b>AmTecs Ltd</b>                                |                    |
| Charnham Park, Hungerford<br>Berkshire, RG17 0YT |                    |
| Tel: +44 (0) 1488 686970                         | sales@amtecs.co.uk |
| Fax: +44 (0) 1488 686968                         | www.amtecs.co.uk   |