



Remarks:

- Glands: 1 off M25 x 1.5 and 1 off M16 x 1.5, Blanking plug 1 off M25 x 1.5
- 2 off 14mm Lifting Hooks (See detail B)

|                         |            |                     |                               |
|-------------------------|------------|---------------------|-------------------------------|
| DRAWN<br>James Souter   | 20/03/2024 | <b>AMTECS LTD</b>   |                               |
| CHECKED<br>Oliver Young | 20/03/2024 |                     |                               |
| QA                      |            | TITLE               |                               |
| MFG                     |            | AMA3-IE3 160M (B35) |                               |
| APPROVED                |            | SIZE<br>A3          | DWG NO<br>AMA3-IE3 160M (B35) |
|                         |            | SCALE<br>1:6        | REV                           |
|                         |            | SHEET 1 OF 1        |                               |

|                   |                                 |
|-------------------|---------------------------------|
| Specification     | <b>IEC 60034-1</b>              |
| Manufacturer      | <b>AmTecs</b>                   |
| Motor type        | <b>AMA3-IE3 160MX2</b>          |
| Rated power       | <b>15 kW S1 Duty</b>            |
| Speed             | <b>2945 rpm</b>                 |
| Voltage           | <b>400V / 690V</b>              |
| Frequency         | <b>50 Hz</b>                    |
| Connection        | <b>Delta / Star</b>             |
| Full load current | <b>26 A / 15.01 A</b>           |
| No-load current   |                                 |
| Enclosure         | <b>IP55</b>                     |
| Insulation class  | <b>F (temp. rise B)</b>         |
| Max. ambient temp | <b>40 °C</b>                    |
| Max. altitude     | <b>1000 mtr above sea level</b> |
| Comment           |                                 |
| Cable entry       | <b>M32 x 1.5</b>                |
| Construction      | <b>Aluminium</b>                |
| Weight            | <b>108 Kg</b>                   |
| Type number       |                                 |
| Warranty          |                                 |

|                             |                 |
|-----------------------------|-----------------|
| Efficiency class            | <b>IE3</b>      |
| Load data                   | <b>100%</b>     |
| Efficiency                  | <b>91.9 %</b>   |
| Power factor                | <b>0.91</b>     |
| Sound pressure level (1m)   | <b>71 dB(A)</b> |
| Resistance R20 (open)       |                 |
| Resistance R20 (Delta)      |                 |
| Full load torque            | <b>48.6 Nm</b>  |
| Starting / Full load torque | <b>1.9</b>      |
| Pull up / Full load torque  |                 |
| Pull out / Full load torque | <b>2.3</b>      |

|                                    |             |
|------------------------------------|-------------|
| Starting / Full load current (DOL) | <b>7</b>    |
| Starting / Full load current (Y/D) |             |
| Rotor Inertia                      |             |
| Bearing DE                         | <b>6209</b> |
| Bearing NDE                        | <b>6209</b> |

|  |                    |
|--|--------------------|
| <b>AmTecs Ltd</b>                                |                    |
| Charnham Park, Hungerford<br>Berkshire, RG17 0YT |                    |
| Tel: +44 (0) 1488 686970                         | sales@amtecs.co.uk |
| Fax: +44 (0) 1488 686968                         | www.amtecs.co.uk   |