


AMA3-IE3 160MX2 (B35)



Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AMA3-IE3 160MX2
Rated power	15 kW S1 Duty
Speed	2945 rpm
Voltage	400V / 690V
Frequency	50 Hz
Connection	Delta / Star
Full load current	26 A / 15.01 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M32 x 1.5
Construction	Aluminium
Weight	108 Kg
Type number	
Warranty	

Efficiency class	IE3	
Load data	100%	
Efficiency	91.9	%
Power factor	0.91	
Sound pressure level (1m)	71	dB(A)
Resistance R20 (open)		
Resistance R20 (Delta)		
Full load torque	48.6	Nm
Starting / Full load torque	1.9	
Pull up / Full load torque		
Pull out / Full load torque	2.3	
Starting / Full load current (DOL)	7	
Starting / Full load current (Y/D)		
Rotor Inertia		
Bearing DE	6209	
Bearing NDE	6209	

MM Engineering Services Ltd Unit 32 Bradford Chamber Business Park Bradford, BD4 8BX Tel: +44 (0) 1274 288777	
	sales@mmengservices.co.uk www.mmengservices.co.uk