



Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AM1-IE2 180M4**
 Rated power **22.2 kW S1 Duty**
 Speed **1758 rpm**
 Voltage **480 / 820V**
 Frequency **60 Hz**
 Connection **Delta / Star**
 Full load current **34 A / 19.7 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M32 x 1.5**
 Construction **Cast Iron**
 Weight **172 Kg**
 Type number
 Warranty

Efficiency class **IE2**
 Load data **100%**
 Efficiency **91.2 %**
 Power factor **0.86**
 Sound pressure level (1m) **81 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)
 Full load torque **121 Nm**
 Starting / Full load torque **2.5**
 Pull up / Full load torque
 Pull out / Full load torque **3.0**
 Starting / Full load current (DOL) **8.3**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6311**
 Bearing NDE **6211**

<p>AmTecs Ltd</p> <p>Charnham Park, Hungerford Berkshire, RG17 0YT</p> <p>Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968</p>		<p>sales@amtecs.co.uk www.amtecs.co.uk</p>
--	--	--