



This drawing serves only as a sketch to show dimensions.
The product delivered may differ. A detailed description of the product can be found below.

| | | |
|--------------------------|--------------|-----|
| AMTECS LTD | | |
| TITLE AM1 (B5) | | |
| SIZE | DWG NO | REV |
| SCALE 1 / 3.5 | SHEET 1 OF 1 | |

Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AM3H-IE3 180LX4**
 Rated power **30 kW S1 Duty**
 Speed **1475 rpm**
 Voltage **400V / 690V**
 Frequency **50 Hz**
 Connection **Delta / Star**
 Full load current **53.8 A / 31.06 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M32 x 1.5**
 Construction **Cast Iron**
 Weight **216 Kg**
 Type number
 Warranty

Efficiency class **IE3**
 Load data **100%**
 Efficiency **93.6 %**
 Power factor **0.86**
 Sound pressure level (1m) **69 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)
 Full load torque **194 Nm**
 Starting / Full load torque **3**
 Pull up / Full load torque
 Pull out / Full load torque **3.6**
 Starting / Full load current (DOL) **9.2**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6311**
 Bearing NDE **6211**

Protection Device **PTC 150**

| | |
|--|--------------------|
| AmTecs Ltd | |
| Charnham Park, Hungerford Berkshire, RG17 0YT | |
| Tel: +44 (0) 1488 686970 | sales@amtecs.co.uk |
| Fax: +44 (0) 1488 686968 | www.amtecs.co.uk |