



Remarks:

1. Glands: 1 off M25 x 1.5 and 1 off M16 x 1.5, Blanking plug 1 off M25 x 1.5
2. 2 off 14mm Lifting Hooks (See detail B)

|          |              |            |                    |                    |
|----------|--------------|------------|--------------------|--------------------|
| DRAWN    | JamesSouter  | 19/03/2024 | AMTECS LTD         |                    |
| CHECKED  | Oliver Young | 20/03/2024 | TITLE              |                    |
| QA       |              |            | AMA3-IE3 160M (B3) |                    |
| MFG      |              |            | SIZE               | DWG NO             |
| APPROVED |              |            | A3                 | AMA3-IE3 160M (B3) |
|          |              |            | SCALE              | 1:6                |
|          |              |            |                    | SHEET 1 OF 1       |

|                   |                                 |
|-------------------|---------------------------------|
| Specification     | <b>IEC 60034-1</b>              |
| Manufacturer      | <b>AmTecs</b>                   |
| Motor type        | <b>AMA3-IE3 160MX2</b>          |
| Rated power       | <b>15 kW S1 Duty</b>            |
| Speed             | <b>2945 rpm</b>                 |
| Voltage           | <b>400V / 690V</b>              |
| Frequency         | <b>50 Hz</b>                    |
| Connection        | <b>Delta / Star</b>             |
| Full load current | <b>26 A / 15.01 A</b>           |
| No-load current   |                                 |
| Enclosure         | <b>IP55</b>                     |
| Insulation class  | <b>F (temp. rise B)</b>         |
| Max. ambient temp | <b>40 °C</b>                    |
| Max. altitude     | <b>1000 mtr above sea level</b> |
| Comment           |                                 |
| Cable entry       | <b>M32 x 1.5</b>                |
| Construction      | <b>Aluminium</b>                |
| Weight            | <b>108 Kg</b>                   |
| Type number       |                                 |
| Warranty          |                                 |

|                             |                 |
|-----------------------------|-----------------|
| Efficiency class            | <b>IE3</b>      |
| Load data                   | <b>100%</b>     |
| Efficiency                  | <b>91.9 %</b>   |
| Power factor                | <b>0.91</b>     |
| Sound pressure level (1m)   | <b>71 dB(A)</b> |
| Resistance R20 (open)       |                 |
| Resistance R20 (Delta)      |                 |
| Full load torque            | <b>48.6 Nm</b>  |
| Starting / Full load torque | <b>1.9</b>      |
| Pull up / Full load torque  |                 |
| Pull out / Full load torque | <b>2.3</b>      |

|                                    |             |
|------------------------------------|-------------|
| Starting / Full load current (DOL) | <b>7</b>    |
| Starting / Full load current (Y/D) |             |
| Rotor Inertia                      |             |
| Bearing DE                         | <b>6209</b> |
| Bearing NDE                        | <b>6209</b> |

|  |   |
|--|---|
| <p><b>AmTecs Ltd</b><br/>                 Charnham Park, Hungerford<br/>                 Berkshire, RG17 0YT<br/>                 Tel: +44 (0) 1488 686970<br/>                 Fax: +44 (0) 1488 686968</p> | <p>sales@amtecs.co.uk<br/>                 www.amtecs.co.uk</p> |
|--|---|