



Specification IEC 60034-1
Manufacturer AmTecs
Motor type AMAS-SR-IE2 100 L2
Rated power 3 kW S1 Duty
Speed 2900 rpm
Voltage 220V
Frequency 50 Hz
Connection Single Phase
Full load current 15.7 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M20 x 1.5
Construction Aluminium
Weight 31.7 Kg
Type number
Warranty
Run Capacitor 40uf/450V
Start Capacitor 500uf/250V

Efficiency class IE2
Load data 100%
Efficiency 84.6 %
Power factor 0.98
Sound pressure level (1m) 83 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)
Full load torque 9.88 Nm
Starting / Full load torque 2.5
Pull up / Full load torque
Pull out / Full load torque 1.9

Starting / Full load current (DOL)
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6206
Bearing NDE 6205

Protection Device Thermal Reset Switch

| | |
|--|--------------------|
| AmTecs Ltd | |
| Charnham Park, Hungerford Berkshire, RG17 0YT | |
| Tel: +44 (0) 1488 686970 | sales@amtecs.co.uk |
| Fax: +44 (0) 1488 686968 | www.amtecs.co.uk |