



**AmTECS LTD**

TITLE: **AM1 (B35)**

SIZE: **A3** DWG NO: \_\_\_\_\_ REV: \_\_\_\_\_

SCALE: **1 / 3.5** SHEET **1** OF **1**

This drawing serves only as a sketch to show dimensions. The product delivered may differ. A detailed description of the product can be found below.

Specification **IEC 60034-1**

Manufacturer **AmTecs**

Motor type **AM3-IE3 355MX2**

Rated power **250 kW S1 Duty**

Speed **2980 rpm**

Voltage **400V / 690V**

Frequency **50 Hz**

Connection **Delta / Star**

Full load current **413.9 A / 240 A**

No-load current

Enclosure **IP55**

Insulation class **F (temp. rise B)**

Max. ambient temp **40 °C**

Max. altitude **1000 mtr above sea level**

Comment

Cable entry **M63 x 1.5**

Construction **Cast Iron**

Weight **1643 Kg**

Type number

Warranty

Efficiency class **IE3**

Load data **100%**

Efficiency **95.8 %**

Power factor **0.91**

Sound pressure level (1m) **100 dB(A)**

Resistance R20 (open)

Resistance R20 (Delta)

Full load torque **801.2 Nm**

Starting / Full load torque **1.7**

Pull up / Full load torque

Pull out / Full load torque **2.3**

Starting / Full load current (DOL) **6.7**

Starting / Full load current (Y/D)

Rotor Inertia

Bearing DE **NU322**

Bearing NDE **6322**

<b>AmTecs Ltd</b>	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk