



Remarks:

- Glands: 1 off M25 x 1.5 and 1 off M16 x 1.5, Blanking plug 1 off M25 x 1.5
- Eye bolt M8

**Specification IEC 60034-1**  
**Manufacturer AmTecs**  
**Motor type AMA3-IE3 112M6**  
**Rated power 2.64 kW S1 Duty**  
**Speed 1158 rpm**  
**Voltage 277 / 480V**  
**Frequency 60 Hz**  
**Connection Delta / Star**  
**Full load current 8.85 A / 5.09 A**  
**No-load current**  
**Enclosure IP55**  
**Insulation class F (temp. rise B)**  
**Max. ambient temp 40 °C**  
**Max. altitude 1000 mtr above sea level**  
**Comment**  
**Cable entry M25 x 1.5**  
**Construction Aluminium**  
**Weight 35.5 Kg**  
**Type number**  
**Warranty**

**Efficiency class IE3**  
**Load data 100%**  
**Efficiency 84.3 %**  
**Power factor 0.74**  
**Sound pressure level (1m) 63 dB(A)**  
**Resistance R20 (open)**  
**Resistance R20 (Delta)**  
**Full load torque 21.8 Nm**  
**Starting / Full load torque 2.2**  
**Pull up / Full load torque**  
**Pull out / Full load torque 2.9**  
**Starting / Full load current (DOL) 7.0**  
**Starting / Full load current (Y/D)**  
**Rotor Inertia**  
**Bearing DE 6306**  
**Bearing NDE 6306**

<b>AmTecs Ltd</b> Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968		sales@amtecs.co.uk www.amtecs.co.uk
---	--	--