



Specification **IEC 60034-1**

Manufacturer **AmTecs**

Motor type **AM3-IE3 315L4**

Rated power **160 kW S1 Duty**

Speed **1480 rpm**

Voltage **400V / 690V**

Frequency **50 Hz**

Connection **Delta / Star**

Full load current **270.9 A / 157 A**

No-load current

Enclosure **IP55**

Insulation class **F (temp. rise B)**

Max. ambient temp **40 °C**

Max. altitude **1000 mtr above sea level**

Comment

Cable entry **M63 x 1.5**

Construction **Cast Iron**

Weight **1078 Kg**

Type number

Warranty

Efficiency class **IE3**

Load data **100%**

Efficiency **95.8 %**

Power factor **0.89**

Sound pressure level (1m) **88 dB(A)**

Resistance R20 (open)

Resistance R20 (Delta)

Full load torque **1032.4 Nm**

Starting / Full load torque **2.5**

Pull up / Full load torque

Pull out / Full load torque **2.7**

Starting / Full load current (DOL) **8.2**

Starting / Full load current (Y/D)

Rotor Inertia

Bearing DE **NU319**

Bearing NDE **6319**

AmTecs Ltd	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk