


AMAB-IE3 132M4 (B35)



Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AMAB-IE3 132M4
Rated power	7.5 kW S1 Duty
Speed	1460 rpm
Voltage	400V / 690V
Frequency	50 Hz
Connection	Delta / Star
Full load current	14.3 A / 8.26 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M25 x 1.5
Construction	Aluminium
Weight	76 Kg
Type number	
Warranty	
Brake Torque	80 (Nm)
Brake Response	0.5 (ms)
Brake Power	87 (W)
Brake Voltage	170

Efficiency class	IE3
Load data	100%
Efficiency	90.4 %
Power factor	0.84
Sound pressure level (1m)	75 dB(A)
Resistance R20 (open)	
Resistance R20 (Delta)	
Full load torque	49.1 Nm
Starting / Full load torque	2
Pull up / Full load torque	
Pull out / Full load torque	2.3

Starting / Full load current (DOL)	8
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	6308
Bearing NDE	6308

MM Engineering Services Ltd	
Unit 32	
Bradford Chamber Business Park	
Bradford, BD4 8BX	sales@mmengservices.co.uk
Tel: +44 (0) 1274 288777	www.mmengservices.co.uk