


AM4-IE4 200LX2 (B5)



Specification IEC 60034-1
Manufacturer AmTecs
Motor type AM4-IE4 200LX2
Rated power 37 kW S1 Duty
Speed 2970 rpm
Voltage 400V / 690V
Frequency 50 Hz
Connection Delta / Star
Full load current 63.3 A / 36.7 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M40 x 1.5
Construction Cast Iron
Weight 262 Kg
Type number
Warranty

Efficiency class IE4
Load data 100%
Efficiency 94.8 %
Power factor 0.89
Sound pressure level (1m) dB(A)
Resistance R20 (open)
Resistance R20 (Delta)
Full load torque 119 Nm
Starting / Full load torque 2.7
Pull up / Full load torque
Pull out / Full load torque 3
Starting / Full load current (DOL) 9
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6212
Bearing NDE 6212

MM Engineering Services Ltd Unit 32 Bradford Chamber Business Park Bradford, BD4 8BX Tel: +44 (0) 1274 288777	sales@mmengservices.co.uk www.mmengservices.co.uk
--	--