


AM3-IE3 100L4 (B35)



Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AM3-IE3 100L4
Rated power	2.2 kW S1 Duty
Speed	1435 rpm
Voltage	220V / 400V
Frequency	50 Hz
Connection	Delta / Star
Full load current	8.11 A / 4.68 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M20 x 1.5
Construction	Cast Iron
Weight	44 Kg
Type number	
Warranty	

Efficiency class	IE3
Load data	100%
Efficiency	86.7 %
Power factor	0.78
Sound pressure level (1m)	56 dB(A)
Resistance R20 (open)	
Resistance R20 (Delta)	

Full load torque	14.6 Nm
Starting / Full load torque	2.5
Pull up / Full load torque	
Pull out / Full load torque	3.5

Starting / Full load current (DOL)	7.2
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	6206
Bearing NDE	6206

MM Engineering Services Ltd Unit 32 Bradford Chamber Business Park Bradford, BD4 8BX Tel: +44 (0) 1274 288777	sales@mmengservices.co.uk www.mmengservices.co.uk
--	--