



Specification IEC 60034-1
Manufacturer AmTecs
Motor type AMAB-IE3 100L4
Rated power 2.2 kW S1 Duty
Speed 1455 rpm
Voltage 220V / 400V
Frequency 50 Hz
Connection Delta / Star
Full load current 7.86 A / 4.52 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M20 x 1.5
Construction Aluminium
Weight 35 Kg
Type number
Warranty
Brake Torque 30 (Nm)
Brake Response 0.35 (ms)
Brake Power 60 (W)
Brake Voltage 99

Efficiency class IE3
Load data 100%
Efficiency 86.7 %
Power factor 0.81
Sound pressure level (1m) 72 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)
Full load torque 14.4 Nm
Starting / Full load torque 2.3
Pull up / Full load torque
Pull out / Full load torque 2.3

Starting / Full load current (DOL) 7.5
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6206
Bearing NDE 6206

| | |
|--|--------------------|
| AmTecs Ltd | |
| Charnham Park, Hungerford Berkshire, RG17 0YT | |
| Tel: +44 (0) 1488 686970 | sales@amtecs.co.uk |
| Fax: +44 (0) 1488 686968 | www.amtecs.co.uk |