


AMAH-IE3 90L2 (B3)



Specification IEC 60034-1
Manufacturer AmTecs
Motor type AMAH-IE3 90L2
Rated power 3 kW S1 Duty
Speed 2910 rpm
Voltage 400V / 690V
Frequency 50 Hz
Connection Delta / Star
Full load current 5.71 A / 3.3 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M20 x 1.5
Construction Aluminium
Weight 22 Kg
Type number
Warranty

Efficiency class IE3
Load data 100%
Efficiency 87.1 %
Power factor 0.87
Sound pressure level (1m) 62 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)
Full load torque 9.85 Nm
Starting / Full load torque 2.2
Pull up / Full load torque
Pull out / Full load torque 3

Starting / Full load current (DOL) 8.5
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6205
Bearing NDE 6205

Protection Device PTC 150

MM Engineering Services Ltd Unit 32 Bradford Chamber Business Park Bradford, BD4 8BX Tel: +44 (0) 1274 288777	
	sales@mmengservices.co.uk www.mmengservices.co.uk