



This drawing serves only as a sketch to show dimensions.  
The product delivered may differ. A detailed description of the product can be found below.

**AMTECS LTD**

TITLE  
**AM1 (B35)**

SIZE  
**A3**

SCALE  
**1 / 3.5**

DWG NO

REV

SHEET 1 OF 1

Specification **IEC 60034-1**

Manufacturer **AmTecs**

Motor type **AM1-IE2 100LX4**

Rated power **3 kW S1 Duty**

Speed **1140 rpm**

Voltage **220V / 400V**

Frequency **50 Hz**

Connection **Delta / Star**

Full load current **10.7 A / 6.2 A**

No-load current

Enclosure **IP55**

Insulation class **F (temp. rise B)**

Max. ambient temp **40 °C**

Max. altitude **1000 mtr above sea level**

Comment

Cable entry **M20 x 1.5**

Construction **Cast Iron**

Weight **47 Kg**

Type number

Warranty

Efficiency class **IE2**

Load data **100%**

Efficiency **85.5 %**

Power factor **0.82**

Sound pressure level (1m) **56 dB(A)**

Resistance R20 (open)

Resistance R20 (Delta)

Full load torque **20 Nm**

Starting / Full load torque **2.6**

Pull up / Full load torque

Pull out / Full load torque **3.3**

Starting / Full load current (DOL) **7.5**

Starting / Full load current (Y/D)

Rotor Inertia

Bearing DE **6206**

Bearing NDE **6206**

<b>AmTecs Ltd</b>	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk