



This drawing serves only as a sketch to show dimensions.  
The product delivered may differ. A detailed description of the product can be found below.

Specification **IEC 60034-1**  
 Manufacturer **AmTecs**  
 Motor type **AMA-HO 132L2**  
 Rated power **15 kW S1 Duty**  
 Speed **2920 rpm**  
 Voltage **400V / 690V**  
 Frequency **50 Hz**  
 Connection **Delta / Star**  
 Full load current **27.49 A / 15.94 A**  
 No-load current  
 Enclosure **IP55**  
 Insulation class **F (temp. rise B)**  
 Max. ambient temp **40 °C**  
 Max. altitude **1000 mtr above sea level**  
 Comment  
 Cable entry **M25 x 1.5**  
 Construction **Aluminium**  
 Weight **61 Kg**  
 Type number  
 Warranty

Efficiency class **N/A**  
 Load data **100%**  
 Efficiency **88.5 %**  
 Power factor **0.89**  
 Sound pressure level (1m) **71 dB(A)**  
 Resistance R20 (open)  
 Resistance R20 (Delta)  
 Full load torque **49.1 Nm**  
 Starting / Full load torque **2.5**  
 Pull up / Full load torque  
 Pull out / Full load torque **2.7**

Starting / Full load current (DOL) **7.5**  
 Starting / Full load current (Y/D)  
 Rotor Inertia  
 Bearing DE **6308**  
 Bearing NDE **6208**

<b>AmTecs Ltd</b>	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk