


AMA3-IE3 160L6 (B5)



Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AMA3-IE3 160L6
Rated power	11 kW S1 Duty
Speed	970 rpm
Voltage	400V / 690V
Frequency	50 Hz
Connection	Delta / Star
Full load current	22 A / 12.7 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M32 x 1.5
Construction	Aluminium
Weight	116 Kg
Type number	
Warranty	

Efficiency class	IE3
Load data	100%
Efficiency	90.3 %
Power factor	0.79
Sound pressure level (1m)	62 dB(A)
Resistance R20 (open)	
Resistance R20 (Delta)	

Full load torque	108.3	Nm
Starting / Full load torque	1.5	
Pull up / Full load torque		
Pull out / Full load torque	2.4	

Starting / Full load current (DOL)	6
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	6
Bearing NDE	6

MM Engineering Services Ltd Unit 32 Bradford Chamber Business Park Bradford, BD4 8BX Tel: +44 (0) 1274 288777	
	sales@mmengservices.co.uk www.mmengservices.co.uk