



Remarks:

- Glands: 1 off M25 x 1.5 and 1 off M16 x 1.5, Blanking plug 1 off M25 x 1.5
- Eye bolt M8

DRAWN James Souter	31/01/2024	AMTECS LTD	
CHECKED Oliver Young	16/02/2024		
QA		AMA3-IE3 132M (B14L)	
MFG		SIZE A3	DWG NO AMA3-IE3 132M (B14L)
APPROVED		SCALE 1:6	REV
		SHEET 1 OF 1	

Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AMA3-IE3 132M6**
 Rated power **4 kW S1 Duty**
 Speed **968 rpm**
 Voltage **400V / 690V**
 Frequency **50 Hz**
 Connection **Delta / Star**
 Full load current **9.4 A / 5.43 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M25 x 1.5**
 Construction **Aluminium**
 Weight **55 Kg**
 Type number
 Warranty

Efficiency class **IE3**
 Load data **100%**
 Efficiency **86.8 %**
 Power factor **0.71**
 Sound pressure level (1m) **59 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)
 Full load torque **39.5 Nm**
 Starting / Full load torque **2.1**
 Pull up / Full load torque
 Pull out / Full load torque **2.6**
 Starting / Full load current (DOL) **5.7**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6308**
 Bearing NDE **6308**

AmTecs Ltd	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk