


AMA3-IE3 100L2 (B14S)



Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AMA3-IE3 100L2
Rated power	3 kW S1 Duty
Speed	2910 rpm
Voltage	220V / 400V
Frequency	50 Hz
Connection	Delta / Star
Full load current	9.9 A / 5.71 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M20 x 1.5
Construction	Aluminium
Weight	30.5 Kg
Type number	
Warranty	

Efficiency class	IE3
Load data	100%
Efficiency	87.1 %
Power factor	0.87
Sound pressure level (1m)	65 dB(A)
Resistance R20 (open)	
Resistance R20 (Delta)	

Full load torque	9.85 Nm
Starting / Full load torque	3.2
Pull up / Full load torque	
Pull out / Full load torque	3.5

Starting / Full load current (DOL)	8.5
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	6206
Bearing NDE	6206

MM Engineering Services Ltd Unit 32 Bradford Chamber Business Park Bradford, BD4 8BX Tel: +44 (0) 1274 288777	sales@mmengservices.co.uk www.mmengservices.co.uk
--	--