



Remarks:

- Glands: 1 off M25 x 1.5 and 1 off M16 x 1.5, Blanking plug 1 off M25 x 1.5
- 2 off 14mm Lifting Hooks (See detail B)

| | | | |
|-------------------------|------------|---------------------|-------------------------------|
| DRAWN James Souter | 20/03/2024 | AMTECS LTD | |
| CHECKED Oliver Young | 20/03/2024 | | |
| QA | | TITLE | |
| MFG | | AMA3-IE3 160M (B35) | |
| APPROVED | | SIZE A3 | DWG NO AMA3-IE3 160M (B35) |
| | | SCALE 1:6 | REV |
| | | SHEET 1 OF 1 | |

| | |
|-------------------|---------------------------------|
| Specification | IEC 60034-1 |
| Manufacturer | AmTecs |
| Motor type | AMA3-IE3 160M2 |
| Rated power | 11 kW S1 Duty |
| Speed | 2945 rpm |
| Voltage | 400V / 690V |
| Frequency | 50 Hz |
| Connection | Delta / Star |
| Full load current | 19.6 A / 11.3 A |
| No-load current | |
| Enclosure | IP55 |
| Insulation class | F (temp. rise B) |
| Max. ambient temp | 40 °C |
| Max. altitude | 1000 mtr above sea level |
| Comment | |
| Cable entry | M32 x 1.5 |
| Construction | Aluminium |
| Weight | 99 Kg |
| Type number | |
| Warranty | |

| | |
|------------------------------------|-----------------|
| Efficiency class | IE3 |
| Load data | 100% |
| Efficiency | 91.2 % |
| Power factor | 0.89 |
| Sound pressure level (1m) | 71 dB(A) |
| Resistance R20 (open) | |
| Resistance R20 (Delta) | |
| Full load torque | 35.7 Nm |
| Starting / Full load torque | 2.2 |
| Pull up / Full load torque | |
| Pull out / Full load torque | 3.6 |
| Starting / Full load current (DOL) | 8.8 |
| Starting / Full load current (Y/D) | |
| Rotor Inertia | |
| Bearing DE | 6209 |
| Bearing NDE | 6209 |

| | |
|---|--|
| AmTecs Ltd Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968 | sales@amtecs.co.uk www.amtecs.co.uk |
|---|--|