


AM4-IE4 315S4 (B5)



Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AM4-IE4 315S4
Rated power	110 kW S1 Duty
Speed	1485 rpm
Voltage	400V / 690V
Frequency	50 Hz
Connection	Delta / Star
Full load current	185.3 A / 107.4 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M63 x 1.5
Construction	Cast Iron
Weight	872 Kg
Type number	
Warranty	

Efficiency class	IE4
Load data	100%
Efficiency	96.3 %
Power factor	0.89
Sound pressure level (1m)	
Resistance R20 (open)	
Resistance R20 (Delta)	
Full load torque	707.4 Nm
Starting / Full load torque	2.5
Pull up / Full load torque	
Pull out / Full load torque	2.7
Starting / Full load current (DOL)	8.5
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	NU319
Bearing NDE	6319

MM Engineering Services Ltd	
Unit 32	
Bradford Chamber Business Park	
Bradford, BD4 8BX	sales@mmengservices.co.uk
Tel: +44 (0) 1274 288777	www.mmengservices.co.uk