AMAS-R 71G2 (B3)

AMTECS



A	B	C	D	E	F	G	H	K	AB	BB	AC	AD	HD	L
112	90	45	14	30	5	11	71	7	245	103	120	109	172	213

AMTECS LTD

TITLE AMAS-R (B3)

SIZE | REV | SHEET 1 OF 1

This drawing serves only as a sketch to show dimensions.
The product delivered may differ. A detailed description of the product can be found below.

Specification	**IEC 60034-1**	Efficiency class	**IE1**
Manufacturer	**AmTecs**	Load data	100%
Motor type	**AMAS-R 71G2**	Efficiency	**70** %
Rated power	**0.55** kW **S1** Duty	Power factor	**0.92**
Speed	**2800** rpm	Sound pressure level (1m)	**75** dB(A)
Voltage	**220V**	Resistance R20 (open)	
Frequency	**50** Hz	Resistance R20 (Delta)	
Connection	**Single Phase**		
Full load current	**3.88 A**	Full load torque	**1.95** Nm
No-load current		Starting / Full load torque	**0.35**
Enclosure	**IP55**	Pull up / Full load torque	
Insulation class	**F (temp. rise B)**	Pull out / Full load torque	**1.7**
Max. ambient temp	**40** °C		
Max. altitude	**1000** mtr above sea level		
Comment			
Cable entry	**M20 x 1.5**	Starting / Full load current (DOL)	
Construction	**Aluminium**	Starting / Full load current (Y/D)	
Weight	**6.5** Kg	Rotor Inertia	
Type number		Bearing DE	**6202**
Warranty		Bearing NDE	**6202**
Run Capacitor	**20uf/450V**		

AmTecs Ltd
Charnham Park, Hungerford
Berkshire, RG17 0YT
Tel: +44 (0) 1488 686970
Fax: +44 (0) 1488 686968
sales@amtecs.co.uk
www.amtecs.co.uk

We make all efforts to better our products. Versions, technical data and figures could be changed therefore. They are not binding before written confirmation.