



Remarks:

- 1. Glands: 1 off M20 x 1.5 and 1 off M16 x 1.5, Blanking plug 1 off M20 x 1.5

DRAWN James Souter	24/01/2024	AMTECS LTD	
CHECKED Oliver Young	29/01/2024		
QA		TITLE	
MFG		AMA3-IE3 90S (B14S)	
APPROVED		SIZE A3	DWG NO AMA3-IE3 90S (B14S)
		SCALE 1 / 4	REV
		SHEET 1 OF 1	

Specification IEC 60034-1
Manufacturer AmTecs
Motor type AMA3-IE3 90S6
Rated power 0.75 kW S1 Duty
Speed 955 rpm
Voltage 220V / 400V
Frequency 50 Hz
Connection Delta / Star
Full load current 3.36 A / 1.93 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M20 x 1.5
Construction Aluminium
Weight 20 Kg
Type number
Warranty

Efficiency class IE3
Load data 100%
Efficiency 78.9 %
Power factor 0.71
Sound pressure level (1m) 51 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)
Full load torque 7.5 Nm
Starting / Full load torque 1.9
Pull up / Full load torque
Pull out / Full load torque 2.3

Starting / Full load current (DOL) 6
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6205
Bearing NDE 6205

AmTecs Ltd	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk