


AM4-IE4 315LX4 (B3)



Specification
Manufacturer
Motor type
Rated power
Speed
Voltage
Frequency
Connection
Full load current
No-load current
Enclosure
Insulation class
Max. ambient temp
Max. altitude
Comment
Cable entry
Construction
Weight
Type number
Warranty

IEC 60034-1
AmTecs
AM4-IE4 315LX4
200 kW S1 Duty
1485 rpm
400V / 690V
50 Hz
Delta / Star
331.7 A / 192.3 A
IP55
F (temp. rise B)
40 °C
1000 mtr above sea level
M63 x 1.5
Cast Iron
1234 Kg

Efficiency class
Load data
Efficiency
Power factor
Sound pressure level (1m)
Resistance R20 (open)
Resistance R20 (Delta)
Full load torque
Starting / Full load torque
Pull up / Full load torque
Pull out / Full load torque

IE4
100%
96.7 %
0.9
dB(A)
1286.2 Nm
2.07
2.5

Starting / Full load current (DOL) **8.5**
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE **NU319**
Bearing NDE **6319**

MM Engineering Services Ltd Unit 32 Bradford Chamber Business Park Bradford, BD4 8BX Tel: +44 (0) 1274 288777	 sales@mmengservices.co.uk www.mmengservices.co.uk
--	--