



This drawing serves only as a sketch to show dimensions.  
The product delivered may differ. A detailed description of the product can be found below.

**AMTECS LTD**

TITLE  
**AM1 (B5)**

SIZE \_\_\_\_\_ DWG NO \_\_\_\_\_ REV \_\_\_\_\_

SCALE 1 / 3.5 SHEET 1 OF 1

Specification **IEC 60034-1**  
 Manufacturer **AmTecs**  
 Motor type **AM3-IE3 90S6**  
 Rated power **0.75 kW S1 Duty**  
 Speed **935 rpm**  
 Voltage **220V / 400V**  
 Frequency **50 Hz**  
 Connection **Delta / Star**  
 Full load current **3.88 A / 2.24 A**  
 No-load current \_\_\_\_\_  
 Enclosure **IP55**  
 Insulation class **F (temp. rise B)**  
 Max. ambient temp **40 °C**  
 Max. altitude **1000 mtr above sea level**  
 Comment \_\_\_\_\_  
 Cable entry **M20 x 1.5**  
 Construction **Cast Iron**  
 Weight **27 Kg**  
 Type number \_\_\_\_\_  
 Warranty \_\_\_\_\_

Efficiency class **IE3**  
 Load data **100%**  
 Efficiency **78.9 %**  
 Power factor **0.61**  
 Sound pressure level (1m) **51 dB(A)**  
 Resistance R20 (open) \_\_\_\_\_  
 Resistance R20 (Delta) \_\_\_\_\_  
 Full load torque **7.66 Nm**  
 Starting / Full load torque **2.5**  
 Pull up / Full load torque \_\_\_\_\_  
 Pull out / Full load torque **3.3**  
 Starting / Full load current (DOL) **4.5**  
 Starting / Full load current (Y/D) \_\_\_\_\_  
 Rotor Inertia \_\_\_\_\_  
 Bearing DE **6205**  
 Bearing NDE **6205**

<b>AmTecs Ltd</b>	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk