


AMAH-IE3 90L2 (B14L)



Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AMAH-IE3 90L2**
 Rated power **3 kW S1 Duty**
 Speed **2910 rpm**
 Voltage **400V / 690V**
 Frequency **50 Hz**
 Connection **Delta / Star**
 Full load current **5.71 A / 3.3 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M20 x 1.5**
 Construction **Aluminium**
 Weight **22 Kg**
 Type number
 Warranty

Efficiency class **IE3**
 Load data **100%**
 Efficiency **87.1 %**
 Power factor **0.87**
 Sound pressure level (1m) **62 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)

Full load torque **9.85 Nm**
 Starting / Full load torque **2.2**
 Pull up / Full load torque
 Pull out / Full load torque **3**

Starting / Full load current (DOL) **8.5**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6205**
 Bearing NDE **6205**

Protection Device **PTC 150**

MM Engineering Services Ltd Unit 32 Bradford Chamber Business Park Bradford, BD4 8BX Tel: +44 (0) 1274 288777	
	sales@mmengservices.co.uk www.mmengservices.co.uk