



Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AMA3-IE3 132S4**
 Rated power **6.6 kW S1 Duty**
 Speed **1752 rpm**
 Voltage **480 / 820V**
 Frequency **60 Hz**
 Connection **Delta / Star**
 Full load current **10.7 A / 6.19 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M25 x 1.5**
 Construction **Aluminium**
 Weight **54.5 Kg**
 Type number
 Warranty

Efficiency class **IE3**
 Load data **100%**
 Efficiency **89.6 %**
 Power factor **0.83**
 Sound pressure level (1m) **66 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)
 Full load torque **36 Nm**
 Starting / Full load torque **2.7**
 Pull up / Full load torque
 Pull out / Full load torque **3.5**
 Starting / Full load current (DOL) **9.1**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6308**
 Bearing NDE **6308**

| | |
|--|--------------------|
| AmTecs Ltd | |
| Charnham Park, Hungerford Berkshire, RG17 0YT | |
| Tel: +44 (0) 1488 686970 | sales@amtecs.co.uk |
| Fax: +44 (0) 1488 686968 | www.amtecs.co.uk |