AMAS-SR-IE2 71 K2 (B14S)



D	E	F	G	H	K	M	N	P	S	T	AC	AD	HD	L
14	30	5	11	71	7	85	70	105	M6	2.5		133	204	250

AMTECS LTD

TITLE AMAS-SR (B14)

SIZE | REV | MY71B14 | SHEET 1 OF 1

This drawing serves only as a sketch to show dimensions.
The product delivered may differ. A detailed description of the product can be found below.

Specification	**IEC 60034-1**	Efficiency class	**IE2**
Manufacturer	**AmTecs**	Load data	100%
Motor type	**AMAS-SR-IE2 71 K2**	Efficiency	**69.5** %
Rated power	**0.37** kW **S1** Duty	Power factor	**0.95**
Speed	**2780** rpm	Sound pressure level (1m)	**70** dB(A)
Voltage	**220V**	Resistance R20 (open)	
Frequency	**50** Hz	Resistance R20 (Delta)	
Connection	**Single Phase**		
Full load current	**2.44 A**	Full load torque	**1.27** Nm
No-load current		Starting / Full load torque	**2.3**
Enclosure	**IP55**	Pull up / Full load torque	
Insulation class	**F (temp. rise B)**	Pull out / Full load torque	**1.8**
Max. ambient temp	**40** °C		
Max. altitude	**1000** mtr above sea level		
Comment			
Cable entry	**M20 x 1.5**	Starting / Full load current (DOL)	
Construction	**Aluminium**	Starting / Full load current (Y/D)	
Weight	**6.6** Kg	Rotor Inertia	
Type number		Bearing DE	**6202**
Warranty		Bearing NDE	**6202**
Run Capacitor	**14uf/450V**		
Start Capacitor	**75uf/250V**		
Protection Device	**Thermal Reset Switch**		

MM Engineering Services Ltd
Unit 32
Bradford Chamber Business Park
Bradford, BD4 8BX
Tel: +44 (0) 1274 288777
sales@mmengservices.co.uk
www.mmengservices.co.uk

We make all efforts to better our products. Versions, technical data and figures could be changed therefore. They are not binding before written confirmation.