



AMTECS LTD

TITLE AMA (B35)		
SIZE	DWG NO	REV
SHEET 1 OF 1		

This drawing serves only as a sketch to show dimensions.
The product delivered may differ. A detailed description of the product can be found below.

Specification IEC 60034-1
Manufacturer AmTecs
Motor type AMAH-IE3 80G2
Rated power 1.5 kW S1 Duty
Speed 2900 rpm
Voltage 220V / 400V
Frequency 50 Hz
Connection Delta / Star
Full load current 5.3 A / 3.06 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M20x1.5
Construction Aluminium
Weight 14.7 Kg
Type number
Warranty

Efficiency class IE3
Load data 100%
Efficiency 84.2 %
Power factor 0.84
Sound pressure level (1m) 58 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)
Full load torque 7.21 Nm
Starting / Full load torque 2.2
Pull up / Full load torque
Pull out / Full load torque 3

Starting / Full load current (DOL) 8.7
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6204
Bearing NDE 6204

Protection Device PTC 150

AmTecs Ltd	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk