



Specification	<b>IEC 60034-1</b>
Manufacturer	<b>AmTecs</b>
Motor type	<b>AM3-IE3 160MX2</b>
Rated power	<b>15 kW S1 Duty</b>
Speed	<b>2940 rpm</b>
Voltage	<b>400V / 690V</b>
Frequency	<b>50 Hz</b>
Connection	<b>Delta / Star</b>
Full load current	<b>26.5 A / 15.3 A</b>
No-load current	
Enclosure	<b>IP55</b>
Insulation class	<b>F (temp. rise B)</b>
Max. ambient temp	<b>40 °C</b>
Max. altitude	<b>1000 mtr above sea level</b>
Comment	
Cable entry	<b>M32 x 1.5</b>
Construction	<b>Cast Iron</b>
Weight	<b>137 Kg</b>
Type number	
Warranty	

Efficiency class	<b>IE3</b>
Load data	<b>100%</b>
Efficiency	<b>91.9 %</b>
Power factor	<b>0.89</b>
Sound pressure level (1m)	<b>81 dB(A)</b>
Resistance R20 (open)	
Resistance R20 (Delta)	
Full load torque	<b>48.7 Nm</b>
Starting / Full load torque	<b>2.6</b>
Pull up / Full load torque	
Pull out / Full load torque	<b>3.6</b>

Starting / Full load current (DOL)	<b>9</b>
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	<b>6209</b>
Bearing NDE	<b>6209</b>

<b>AmTecs Ltd</b>	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk