



Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AMAB-IE2 71G2**
 Rated power **0.66 kW S1 Duty**
 Speed **3384 rpm**
 Voltage **277 / 480V**
 Frequency **60 Hz**
 Connection **Delta / Star**
 Full load current **2.27 A / 1.31 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M20 x 1.5**
 Construction **Aluminium**
 Weight **8.3 Kg**
 Type number
 Warranty
 Brake Torque **6 (Nm)**
 Brake Response **0.3 (ms)**
 Brake Power **28 (W)**
 Brake Voltage **99**

Efficiency class **IE2**
 Load data **100%**
 Efficiency **74.1 %**
 Power factor **0.82**
 Sound pressure level (1m) **69 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)
 Full load torque **1.86 Nm**
 Starting / Full load torque **2.3**
 Pull up / Full load torque
 Pull out / Full load torque **2.2**

Starting / Full load current (DOL) **7.4**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6202**
 Bearing NDE **6202**

AmTecs Ltd	
Charnham Park, Hungerford Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk