




Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AMA-IE2 71K2
Rated power	0.37 kW S1 Duty
Speed	2800 rpm
Voltage	220V / 400V
Frequency	50 Hz
Connection	Delta / Star
Full load current	1.65 A / 0.95 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M20 x 1.5
Construction	Aluminium
Weight	6.5 Kg
Type number	
Warranty	

Efficiency class	IE2
Load data	100%
Efficiency	69.5 %
Power factor	0.81
Sound pressure level (1m)	62 dB(A)
Resistance R20 (open)	
Resistance R20 (Delta)	

Full load torque	1.3	Nm
Starting / Full load torque	2.8	
Pull up / Full load torque		
Pull out / Full load torque	3	

Starting / Full load current (DOL)	7
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	6202
Bearing NDE	6202

AmTecs Ltd Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968	
	sales@amtecs.co.uk www.amtecs.co.uk