




Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AMA-IE2 80K2
Rated power	0.9 kW S1 Duty
Speed	3450 rpm
Voltage	277 / 480V
Frequency	60 Hz
Connection	Delta / Star
Full load current	2.93 A / 1.69 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M20x1.5
Construction	Aluminium
Weight	12 Kg
Type number	
Warranty	

Efficiency class	IE2
Load data	100%
Efficiency	77.4 %
Power factor	0.83
Sound pressure level (1m)	63 dB(A)
Resistance R20 (open)	
Resistance R20 (Delta)	
Full load torque	2.5 Nm
Starting / Full load torque	2.7
Pull up / Full load torque	
Pull out / Full load torque	3.7

Starting / Full load current (DOL)	8.5
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	6204
Bearing NDE	6204

AmTecs Ltd	
Charnham Park, Hungerford	
Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk