




Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AMAS-R-IE2 90 S4**
 Rated power **1.1 kW S1 Duty**
 Speed **1400 rpm**
 Voltage **220V**
 Frequency **50 Hz**
 Connection **Single Phase**
 Full load current **6.2 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M20 x 1.5**
 Construction **Aluminium**
 Weight **16.7 Kg**
 Type number
 Warranty
 Run Capacitor **30uf/450V**

Efficiency class **IE2**
 Load data **100%**
 Efficiency **81.4 %**
 Power factor **0.95**
 Sound pressure level (1m) **78 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)

Full load torque **7.5 Nm**
 Starting / Full load torque **0.4**
 Pull up / Full load torque
 Pull out / Full load torque **1.9**

Starting / Full load current (DOL)
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6205**
 Bearing NDE **6204**

Protection Device **Thermal Reset Switch**

AmTecs Ltd Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968	
	sales@amtecs.co.uk www.amtecs.co.uk