




Specification
Manufacturer AmTecs
Motor type AMAH-IE3 90L4
Rated power 2.2 kW S1 Duty
Speed 1455 rpm
Voltage 220V / 400V
Frequency 50 Hz
Connection Delta / Star
Full load current 7.83 A / 4.52 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M20 x 1.5
Construction Aluminium
Weight 23 Kg
Type number
Warranty

Efficiency class IE3
Load data 100%
Efficiency 86.7 %
Power factor 0.81
Sound pressure level (1m) 54 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)

Full load torque 14.4 Nm
Starting / Full load torque 2.2
Pull up / Full load torque
Pull out / Full load torque 2.5

Starting / Full load current (DOL) 8.1
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6205
Bearing NDE 6205

Protection Device PTC 150

AmTecs Ltd Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968	
	sales@amtecs.co.uk www.amtecs.co.uk