




Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AM3-IE3 225M8
Rated power	22 kW S1 Duty
Speed	740 rpm
Voltage	400V / 690V
Frequency	50 Hz
Connection	Delta / Star
Full load current	44.9 A / 26 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M40 x 1.5
Construction	Cast Iron
Weight	312 Kg
Type number	
Warranty	

Efficiency class	IE3
Load data	100%
Efficiency	90.6 %
Power factor	0.78
Sound pressure level (1m)	73 dB(A)
Resistance R20 (open)	
Resistance R20 (Delta)	

Full load torque	283.9 Nm
Starting / Full load torque	2.1
Pull up / Full load torque	
Pull out / Full load torque	2.6

Starting / Full load current (DOL)	6.7
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	6313
Bearing NDE	6312

AmTecs Ltd Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968	
	sales@amtecs.co.uk www.amtecs.co.uk