




Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AMA3-IE3 100LX8
Rated power	1.32 kW S1 Duty
Speed	852 rpm
Voltage	277 / 480V
Frequency	60 Hz
Connection	Delta / Star
Full load current	5.15 A / 2.96 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M20 x 1.5
Construction	Aluminium
Weight	Kg
Type number	
Warranty	

Efficiency class	IE3
Load data	100%
Efficiency	77.7 %
Power factor	0.69
Sound pressure level (1m)	54 dB(A)
Resistance R20 (open)	
Resistance R20 (Delta)	
Full load torque	14.8 Nm
Starting / Full load torque	1.8
Pull up / Full load torque	
Pull out / Full load torque	2.0

Starting / Full load current (DOL)	6.6
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	6206
Bearing NDE	6206

AmTecs Ltd Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968	sales@amtecs.co.uk www.amtecs.co.uk
---	--