




Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AM1-IE2 100L2
Rated power	3.6 kW S1 Duty
Speed	3469.2pm
Voltage	277 / 480V
Frequency	60 Hz
Connection	Delta / Star
Full load current	10.1 A / 5.9 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M20 x 1.5
Construction	Cast Iron
Weight	41 Kg
Type number	
Warranty	

Efficiency class	IE2
Load data	100%
Efficiency	84.6 %
Power factor	0.87
Sound pressure level (1m)	70 dB(A)
Resistance R20 (open)	
Resistance R20 (Delta)	

Full load torque	10 Nm
Starting / Full load torque	3.1
Pull up / Full load torque	
Pull out / Full load torque	3.9

Starting / Full load current (DOL)	8.5
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	6206
Bearing NDE	6206

AmTecs Ltd	
Charnham Park, Hungerford	
Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk