




This drawing serves only as a sketch to show dimensions.
The product delivered may differ. A detailed description of the product can be found below.

Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AMAB-IE3 80K2
Rated power	0.9 kW S1 Duty
Speed	3480 rpm
Voltage	277 / 480V
Frequency	60 Hz
Connection	Delta / Star
Full load current	2.85 A / 1.64 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M20x1.5
Construction	Aluminium
Weight	11.6 Kg
Type number	
Warranty	
Brake Torque	8 (Nm)
Brake Response	0.3 (ms)
Brake Power	28 (W)
Brake Voltage	99

Efficiency class	IE3
Load data	100%
Efficiency	80.7 %
Power factor	0.82
Sound pressure level (1m)	70 dB(A)
Resistance R20 (open)	
Resistance R20 (Delta)	

Full load torque	2.47 Nm
Starting / Full load torque	2.3
Pull up / Full load torque	
Pull out / Full load torque	2.3

Starting / Full load current (DOL)	7.4
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	6204
Bearing NDE	6204

AmTecs Ltd Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968	
	sales@amtecs.co.uk www.amtecs.co.uk