




Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AMA-IE2 71K6**
 Rated power **0.18 kW S1 Duty**
 Speed **920 rpm**
 Voltage **220V / 400V**
 Frequency **50 Hz**
 Connection **Delta / Star**
 Full load current **1.27 A / 0.73 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M20 x 1.5**
 Construction **Aluminium**
 Weight **6.5 Kg**
 Type number
 Warranty

Efficiency class **IE2**
 Load data **100%**
 Efficiency **56.6 %**
 Power factor **0.63**
 Sound pressure level (1m) **54 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)

Full load torque **1.9 Nm**
 Starting / Full load torque **2.3**
 Pull up / Full load torque
 Pull out / Full load torque **2.5**

Starting / Full load current (DOL) **3.5**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6202**
 Bearing NDE **6202**

AmTecs Ltd

Charnham Park, Hungerford
 Berkshire, RG17 0YT

Tel: +44 (0) 1488 686970

Fax: +44 (0) 1488 686968

sales@amtecs.co.uk

www.amtecs.co.uk