




Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AMAH-IE3 132M2
Rated power	9.2 kW S1 Duty
Speed	2930 rpm
Voltage	400V / 690V
Frequency	50 Hz
Connection	Delta / Star
Full load current	16.7 A / 9.64 A
No-load current	
Enclosure	IP55
Insulation class	F (temp. rise B)
Max. ambient temp	40 °C
Max. altitude	1000 mtr above sea level
Comment	
Cable entry	M25 x 1.5
Construction	Aluminium
Weight	55 Kg
Type number	
Warranty	

Efficiency class	IE3
Load data	100%
Efficiency	90.6 %
Power factor	0.88
Sound pressure level (1m)	70 dB(A)
Resistance R20 (open)	
Resistance R20 (Delta)	

Full load torque	30 Nm
Starting / Full load torque	2.2
Pull up / Full load torque	
Pull out / Full load torque	3.2

Starting / Full load current (DOL)	8.8
Starting / Full load current (Y/D)	
Rotor Inertia	
Bearing DE	6308
Bearing NDE	6308

Protection Device **PTC 150**

AmTecs Ltd

Charnham Park, Hungerford
Berkshire, RG17 0YT

Tel: +44 (0) 1488 686970

Fax: +44 (0) 1488 686968

sales@amtecs.co.uk

www.amtecs.co.uk