




Specification
Manufacturer AmTecs
Motor type AMA-IE2 132M4
Rated power 9 kW S1 Duty
Speed 1746 rpm
Voltage 480 / 820V
Frequency 60 Hz
Connection Delta / Star
Full load current 14.7 A / 8.52 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M25 x 1.5
Construction Aluminium
Weight 64 Kg
Type number
Warranty

Efficiency class IE2
Load data 100%
Efficiency 88.7 %
Power factor 0.84
Sound pressure level (1m) 66 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)

Full load torque 49.2 Nm
Starting / Full load torque 2.7
Pull up / Full load torque
Pull out / Full load torque 2.9

Starting / Full load current (DOL) 8.0
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6308
Bearing NDE 6308

AmTecs Ltd Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968	
	sales@amtecs.co.uk www.amtecs.co.uk