




Specification
Manufacturer AmTecs
Motor type AMAH-IE3 71G2
Rated power 0.75 kW S1 Duty
Speed 2900 rpm
Voltage 220V / 400V
Frequency 50 Hz
Connection Delta / Star
Full load current 2.94 A / 1.7 A
No-load current
Enclosure IP55
Insulation class F (temp. rise B)
Max. ambient temp 40 °C
Max. altitude 1000 mtr above sea level
Comment
Cable entry M20 x 1.5
Construction Aluminium
Weight 8.7 Kg
Type number
Warranty

Efficiency class IE3
Load data 100%
Efficiency 80.7 %
Power factor 0.79
Sound pressure level (1m) 54 dB(A)
Resistance R20 (open)
Resistance R20 (Delta)

Full load torque 2.5 Nm
Starting / Full load torque 2.8
Pull up / Full load torque
Pull out / Full load torque 2.6

Starting / Full load current (DOL) 8
Starting / Full load current (Y/D)
Rotor Inertia
Bearing DE 6202
Bearing NDE 6202

Protection Device PTC 150

AmTecs Ltd Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968	
	sales@amtecs.co.uk www.amtecs.co.uk