AMA3-IE3 80G2 (B14S)

AMTECS



Remarks:

1. Glands: 1 off M20 x 1.5 and 1 off M16 x 1.5, Blanking plug 1 off M20 x 1.5

DRAWN	JamesSouter	25/01/2024	AMTECS LTD
CHECKED	Oliver Young	26/01/2024	TITLE: AMA3-IE3 80 (B14S)
QA			
MFG			
APPROVED			SIZE A3 / DWG NO AMA3-IE3 80 (B14S) / REV
			SCALE 1 / 4 / SHEET 1 OF 1

Specification	**IEC 60034-1**	Efficiency class	**IE3**
Manufacturer	**AmTecs**	Load data	100%
Motor type	**AMA3-IE3 80G2**	Efficiency	**82.7** %
Rated power	**1.32** kW **S1** Duty	Power factor	**0.83**
Speed	**3492** rpm	Sound pressure level (1m)	**63** dB(A)
Voltage	**277 / 480V**	Resistance R20 (open)	
Frequency	**60** Hz	Resistance R20 (Delta)	
Connection	**Delta / Star**		
Full load current	**4.02 A / 2.31 A**	Full load torque	**3.61** Nm
No-load current		Starting / Full load torque	**2.5**
Enclosure	**IP55**	Pull up / Full load torque	
Insulation class	**F (temp. rise B)**	Pull out / Full load torque	**3.4**
Max. ambient temp	**40** °C		
Max. altitude	**1000** mtr above sea level		
Comment			
Cable entry	**M20x1.5**	Starting / Full load current (DOL)	**9.2**
Construction	**Aluminium**	Starting / Full load current (Y/D)	
Weight	**15** Kg	Rotor Inertia	
Type number		Bearing DE	**6204**
Warranty		Bearing NDE	**6204**

AmTecs Ltd
Charnham Park, Hungerford
Berkshire, RG17 0YT
Tel: +44 (0) 1488 686970
Fax: +44 (0) 1488 686968
sales@amtecs.co.uk
www.amtecs.co.uk

We make all efforts to better our products. Versions, technical data and figures could be changed therefore. They are not binding before written confirmation.