




Specification **IEC 60034-1**
 Manufacturer **AmTecs**
 Motor type **AMA-IE2 63K4**
 Rated power **0.144 kW S1 Duty**
 Speed **1632 rpm**
 Voltage **277 / 480V**
 Frequency **60 Hz**
 Connection **Delta / Star**
 Full load current **0.73 A / 0.42 A**
 No-load current
 Enclosure **IP55**
 Insulation class **F (temp. rise B)**
 Max. ambient temp **40 °C**
 Max. altitude **1000 mtr above sea level**
 Comment
 Cable entry **M20 x 1.5**
 Construction **Aluminium**
 Weight **4 Kg**
 Type number
 Warranty

Efficiency class **IE2**
 Load data **100%**
 Efficiency **59.1 %**
 Power factor **0.71**
 Sound pressure level (1m) **60 dB(A)**
 Resistance R20 (open)
 Resistance R20 (Delta)

Full load torque **0.8 Nm**
 Starting / Full load torque **2.2**
 Pull up / Full load torque
 Pull out / Full load torque **2.4**

Starting / Full load current (DOL) **4.8**
 Starting / Full load current (Y/D)
 Rotor Inertia
 Bearing DE **6201**
 Bearing NDE **6201**

AmTecs Ltd Charnham Park, Hungerford Berkshire, RG17 0YT Tel: +44 (0) 1488 686970 Fax: +44 (0) 1488 686968	
	sales@amtecs.co.uk www.amtecs.co.uk