




**Specification**  
**Manufacturer** AmTecs  
**Motor type** AMAH-IE3 90L4  
**Rated power** 2.2 kW S1 Duty  
**Speed** 1455 rpm  
**Voltage** 220V / 400V  
**Frequency** 50 Hz  
**Connection** Delta / Star  
**Full load current** 7.83 A / 4.52 A  
**No-load current**  
**Enclosure** IP55  
**Insulation class** F (temp. rise B)  
**Max. ambient temp** 40 °C  
**Max. altitude** 1000 mtr above sea level  
**Comment**  
**Cable entry** M20 x 1.5  
**Construction** Aluminium  
**Weight** 23 Kg  
**Type number**  
**Warranty**

**Efficiency class** IE3  
**Load data** 100%  
**Efficiency** 86.7 %  
**Power factor** 0.81  
**Sound pressure level (1m)** 54 dB(A)  
**Resistance R20 (open)**  
**Resistance R20 (Delta)**

**Full load torque** 14.4 Nm  
**Starting / Full load torque** 2.2  
**Pull up / Full load torque**  
**Pull out / Full load torque** 2.5

**Starting / Full load current (DOL)** 8.1  
**Starting / Full load current (Y/D)**  
**Rotor Inertia**  
**Bearing DE** 6205  
**Bearing NDE** 6205

**Protection Device** PTC 150

**AmTecs Ltd**

Charnham Park, Hungerford  
Berkshire, RG17 0YT

Tel: +44 (0) 1488 686970

Fax: +44 (0) 1488 686968

sales@amtecs.co.uk

www.amtecs.co.uk