




Specification **IEC 60034-1**

Manufacturer **AmTecs**

Motor type **AM3-IE3 250M6**

Rated power **44.4 kW S1 Duty**

Speed **1182 rpm**

Voltage **480 / 820V**

Frequency **60 Hz**

Connection **Delta / Star**

Full load current **68.1 A / 39.5 A**

No-load current

Enclosure **IP55**

Insulation class **F (temp. rise B)**

Max. ambient temp **40 °C**

Max. altitude **1000 mtr above sea level**

Comment

Cable entry **M63 x 1.5**

Construction **Cast Iron**

Weight **398 Kg**

Type number

Warranty

Efficiency class **IE3**

Load data **100%**

Efficiency **93.3 %**

Power factor **0.84**

Sound pressure level (1m) **81 dB(A)**

Resistance R20 (open)

Resistance R20 (Delta)

Full load torque **358.7 Nm**

Starting / Full load torque **2.1**

Pull up / Full load torque

Pull out / Full load torque **2.3**

Starting / Full load current (DOL) **7.2**

Starting / Full load current (Y/D)

Rotor Inertia

Bearing DE **6314**

Bearing NDE **6313**

|                                                  |                    |
|--------------------------------------------------|--------------------|
| <b>AmTecs Ltd</b>                                |                    |
| Charnham Park, Hungerford<br>Berkshire, RG17 0YT |                    |
| Tel: +44 (0) 1488 686970                         | sales@amtecs.co.uk |
| Fax: +44 (0) 1488 686968                         | www.amtecs.co.uk   |